

# DÜO

## ON-SITE GENERATOR

- SIMPLE
- SAFE
- COST-EFFECTIVE



The Paerosol Düo system is the future of On-Site Generation: Save time and money with on-site production of all natural, ready-to-use cleaning & disinfecting solutions.

### SECURITY

- Prevent tampering with pre-installed locks

### POWER DISPLAY

- Easy-to-monitor current flow

### SIMPLE TO USE

- On / Off Switch
- Clean / Flush Control

### EASY INSTALLATION

- Only requires a water supply, power and drain
- Portable or wall mounted for easy access and usability
- Direct access to Paerolyte & PaeroClean supply tanks

### EXTERNAL FLOW METER

- Easy-to-monitor water flow rate



**FILLS SPRAY BOTTLES**

**FILLS EQUIPMENT**

## Paerolyte

- Broad spectrum disinfectant
- Food & non-food surface sanitizer
- Deodorizer
- Safe, all-natural, non-toxic



### REPLACES:

- Chemical-based disinfectants / sanitizers
- Multi-surface sanitizers



### REPLACES:

- Chemical cleaner / disinfectants and surface sanitizers in:
  - Mop buckets
  - Flat microfiber mop systems
  - Automatic scrubbers

**ONE GENERATOR  
+  
FOUR SOLUTIONS  
=**

**DISINFECTANT  
SANITIZER  
DEGREASER  
CLEANER**

### REPLACES:

- Chemical-based cleaners
- All-purpose cleaning solutions
- Carpet / glass / stainless steel cleaners



### REPLACES:

- Chemical-based concentrates
- Hard surface cleaners in:
  - Mop buckets
  - Flat microfiber mop systems
  - Automatic scrubbers

## PaeroClean

- All-purpose, multi-surface cleaner
- Powerful degreaser & drain cleaner
- Safe, all-natural, non-toxic

## Düo Specifications

| Dispensing System   | Paerolyte  | PaeroClean   |
|---------------------|--|--|
| Dilution Ratio      | Broad Spectrum Disinfectant: Full Strength<br>Daily Sanitizer: 1.5:1 / Food Rinse: 5:1 | Degreaser / Drain Cleaner: Full Strength<br>All Purpose Cleaner: 5:1 |
| pH                  | 6.2 - 7.0  | 10.5 - 11.5  |
| Generation System   | Paerolyte  | PaeroClean   |
| Generation rate     | 10 Gal/38L per hr  | 5 Gal/19 L per hr  |
| Dimensions / Weight | Düo  | Power Requirements   |
| Depth               | 10 in/254 mm   | Circuit requirement (min): 15A<br>Input AC voltage:<br>120V/60Hz     |
| Width               | 20 in/508 mm   |  |
| Height              | 24 in/609 mm   |  |
| Weight              | 40 lbs/18 kg   |  |

Paerosol LLC, 875 Walt Miller Street, Suite A1, Mount Pleasant, SC 29464  
+1 843 535 0500 • www.paerosol.com

